Greater stability and reliability, with ± 0.02 pH accuracy over long periods of time. Virtually drift resistant, saving valuable time by reducing calibration frequency while maximizing up-time!

Thermo Scientific Orion 2001SC

High Purity ROSS® pH Electrode





Markets

- Power Generation
- Pulp and Paper
- Semiconductor
- Pharmaceutical
- Drinking Water

Applications

- Boiler Water
- Condensate
- Bottling Water
- Municipal Water
- Water for Injection
- Water for Fabrication

High Purity Water pH Measurements with Complete Assurance

The Thermo Scientific Orion 2001SC high purity ROSS pH electrode is a combination electrode designed for online applications when the highest accuracy and precision are required. The pH sensing and reference electrodes are combined into a single electrode best suited for high purity measurements. The 2001SC electrode is designed to be used in the Thermo Scientific Orion stainless steel flow cell, which holds and positions the electrode for optimal results.

The 2001SC high purity ROSS pH electrode is a research-grade electrode engineered specifically for use in online pH measurement applications. It is designed with a sidearm, for attachment to a reservoir of specially formulated ROSS reference filling solution. This ensures the outer reference chamber is always full, allowing the ceramic liquid junction to flow freely.

With its unique internal element system, the high purity ROSS pH electrode provides superior stability, faster response and greater accuracy than other conventional electrodes with silver chloride or calomel internal systems. The electrode response is fast; even in samples varying by 50 °C or more. Drift is less than 0.002 pH units per day, eliminating the need for frequent standardization.

The ROSS internal system is designed to have virtually zero temperature coefficient, that is, the potential difference between the elements is zero regardless of the difference in the temperature of the elements. The internal elements of the combination pH electrodes are housed in an electrode body that, in use, is partially immersed in the sample and partially exposed to the ambient air. Thus, the internal elements may be at different temperatures.











2001SC High Purity ROSS Electrode Benefits

- Unmatched drift-free reference system — with precision of 0.02 pH
- Reliable, reproducible results in high purity samples
- Fastest response for online pH electrodes
- Unparalleled pH response to temperature changes
- Eliminates junction potential problems associated with conventional electrodes
- Industry leading UPW pH sensor technology is compatible with standard terminal connections on most pH controllers

| Specifications | |
|------------------------|--|
| pH Range | 0 to 14 pH |
| Temperature Range | 0 to 100 °C |
| Drift | Less than 0.002 pH units |
| Slope | 92 to 102% (54.4 to 60.3 mV/dec) |
| Isopotential Point | pH 7 |
| Junction | Ceramic frit |
| Internal Reference | ROSS |
| | |
| Size | Electrode Diameter: 12 mm Electrode Length: 125 mm Electrode Cap Diameter: 16 mm Electrode Cap Length: 30 mm |
| Size Detachable Cable | Electrode Length: 125 mm Electrode Cap Diameter: 16 mm |
| | Electrode Length: 125 mm Electrode Cap Diameter: 16 mm Electrode Cap Length: 30 mm |
| Detachable Cable | Electrode Length: 125 mm Electrode Cap Diameter: 16 mm Electrode Cap Length: 30 mm Coaxial |

| Cat. No. | Description |
|----------|--|
| 2001SC | High purity ROSS glass pH electrode with screw cap connector (Requires additional purchase of ATC probe and electrode cable) |
| 2001FS | ROSS internal fill solution, (5) x 2 oz. bottles |
| 2001F4 | ROSS internal fill solution, (4) x 4 oz. bottles |
| 2001FC | Stainless steel (316) flow cell with mounting bracket |
| 2001EC | Electrode cable, 1 meter (screw cap to tinned leads) |
| 20015M | Electrode cable, 5 meter (screw cap to tinned leads) |
| 2001XM | Electrode cable, 10 meter (screw cap to tinned leads) |
| 2001TM | ATC probe, stainless steel, PT1000, 5 meter cable (tinned leads) |
| 2001TP | ATC probe, stainless steel, NTC 30k ohm, 1 meter cable (tinned leads) |
| 910104 | pH 4.01 buffer, 475 mL bottle |
| 910107 | pH 7.00 buffer, 475 mL bottle |
| 910110 | pH 10.01 buffer, 475 mL bottle |
| 810001 | ROSS pH electrode storage solution, 475 mL bottle |
| 900021 | pH cleaning solution A for protein contaminants, 4 x 30 mL bottles |
| 900022 | pH cleaning solution B for general cleaning and bacterial contaminants, 4 x 60 mL bottles |
| 900023 | pH cleaning solution C for general cleaning, 4 x 30 mL bottles |
| 900024 | pH cleaning solution D for oil and grease contaminants, 4 x 60 mL bottles |
| | |

For more information or to contact your local Thermo Scientific water quality specialist, call 1-800-225-1480 or visit our website at www.thermo.com/process.

©2009 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. ROSS and the COIL tradedress are trademarks of Thermo Fisher Scientific Inc. US Patent 6,793,787.



North America

166 Cummings Center Beverly, MA 01915 USA Toll Free: 1-800-225-1480 Tel: 1-978-232-6000 Dom. Fax: 1-978-232-6015 Int'l Fax: 978-232-6031

Europe P.O. Box 254, 3860 AG Nijkerk Wallerstraat 125K, 3862 CN Nijkerk, Netherlands Tel: (31) 033-2463887 Fax: (31) 033-2460832

Asia Pacific

Blk 55, Ayer Rajah Crescent #04-16/24, Singapore 139949 Tel: 65-6778-6876 Fax: 65-6773-0836

www.thermo.com/processwater



S-2001SC-E 0609 RevC

